

FLUSHING SYSTEMS

FOR W.C. TANKS

Filling valves provide water to the W.C. tank.

Three types available:
for lateral water entrance,
inferior and double water
entrance.

Flushing water discharges
are designed for
WATER SAVING.

Available in two options:
with *start/stop* button
(water volumen at will)
and double button
(two different water
volumes),
this one also available
as flushing wall hanging.



¡WATER SAVING!

REFERENCES

REF.	DESCRIPTION	EAN
236000	Flushing system (lateral) W.C. - brass thread	8435084024819
236200	Flushing system (lateral) W.C. - plastic thread	8435084024833
236100	Flushing system (inferior) W.C. - brass thread	8435084024826
236300	Flushing system (inferior) W.C. - plastic thread	8435084024840
236600	Flushing system (universal) W.C. - brass thread	8435084024871

Easy to install - Filling at will



REF.	DESCRIPTION	EAN
236700	Dual flushing W.C. (minimal 3 litres)	8435084024888
236800	Start/stop flushing W.C.	8435084024895
236900	Flushing wall hanging W.C. (dual, minimal 3 litres)	8435084024901

Selection of water volumen to discharge



Guarantee: 2 years.

Obeys all quality regulations from the European Union.



Rafael Márquez Moro y Cía, S.A.

C/ del Sol, 22 - Pol. Ind. Armenteres

08980 Sant Feliu de Llobregat - Barcelona (Spain)

Tel. +34 93 666 0325 Fax + 3493 666 1117 export@rmmcia.com

www.rmmcia.com



Nº ES08/5687